



In-Band Flow Establishment for End-to-End QoS in RDRN

Saravanan Radhakrishnan


Organization

- Introduction
- Motivation
- QoS architecture
- Flow Establishment Protocol
- QoS Layer
- Experiments and Results
- Conclusion and Future Work



Introduction - QoS

- Best Effort
 - No guarantees
 - All packets are treated equally
- Service Differentiation
 - Consistent Service Quality
 - End-to-end guarantees
- Components of service quality
 - Throughput, Jitter, Delay and Reliability




QoS in Wireless Mobile systems

- QoS provisioning in wireless mobile systems is very challenging because of
 - Wireless channel characteristics
 - Mobility
- Wireless Channel Characteristics
 - High Bit Error Rate, which results in packet loss, which in turn translates into delay and jitter
- Mobility
 - Roaming node changes point of connectivity, resulting in resource fluctuation




Introduction - RDRN

- Rapidly Deployable Radio Networks (RDRN) is
 - multi-hop wireless ATM network.
 - highly dynamic networking environment.
- RDRN consists of
 - a low bandwidth, high reliability, omni-directional orderwire link, for node discovery and topology configuration.
 - a high bandwidth radio link for high speed data transfer.
- RDRN consists of two types of nodes
 - Mobile Access Point (MAP)
 - Mobile Node (MN)




RDRN Protocol Stack

Application
TCP/UDP
IP
CLIP/SWITCH
AAL
SAR
DLC
Virtual Device
Physical Device




Motivation

- Propose, Implement and Evaluate a QoS Architecture for RDRN
- Existing QoS architectures are not suited for a highly dynamic networking environment like RDRN.
 - Integrated Services
 - Differentiated Services



Motivation

- Out-of-Band Signaling is not efficient for highly dynamic networking environments like RDRN because
 - High Signaling overhead involved in connection setup.
 - Link failures result in connection breakdown. Re-establishment of the connection involves more signaling overhead
- ATM not suited to handle dynamic conditions that arise in the network.
- IP is robust, therefore it is more suited to handle mobility.
- Need to differentiate and prioritize traffic based on the requirements of the application.




QoS Architecture - Requirements

- Configure, predict and maintain the requested QoS during the lifetime of the flow.
- Shield the application from the complexity of the underlying QoS specification.
- Set up resources in all the MAPs from the source to the destination, i.e., set up an end-to-end flow.




RDRN QoS Architecture





RDRN QoS Arch (contd.)

- Flow Management Block
 - QoS Mapping
 - Flow Establishment
 - Resource Management
- QoS Layer
 - Classifier
 - Traffic Shaper
 - Scheduler



Flow Management



Flow Establishment

- *In-Band* Signaling, i.e., end-to-end flows are established along with the transfer of data.
- Flows are established through the introduction of a new IP option field, referred to as the *RDRN QoS* option field.
- Uses the robustness of IP to handle the dynamic conditions that arise in the network.
- Uses ATM for layer 2 switching.
- Sets up resources for the flow, in all the nodes from the source to the destination.



RDRN QoS Option Field


REQ/RES	MAX/MIN/BEST	ALLOC/DE-ALLOC	VPI	VCI
1	2	1	16	16

REQ/RES - To indicate if resources have been allocated for this.


MAX/MIN/BEST - To specify the requirements of the flow.

ALLOC/DE-ALLOC - To allocate/de-allocate resources for the flow



VPI/VCI - Specific VPI/VCI that will be used for this flow.




Flow Establishment




QoS Report




A Short Demo



Demo - Test Configuration




Flow Re-Establishment Failure of Link




Flow Re-Establishment

Re-assembly of IP datagram




QoS Report




Flow Re-Establishment


Re-establishment of end-to-end flow




Flow Re-Establishment Link Layer Switching



A Video Clipping




Test Scenario



QoS Layer

- Provides QoS at the ATM layer.
- Does multiplexing of cells.
- Receives a train of ATM cells from the SAR layer and puts them in the appropriate queue based on the priority.
- Weighted Round Robin Scheduler to schedule the transmission of cells.
- A train of cells sent to the DLC layer for framing and transmission.




Revised RDRN Protocol Stack

Application
TCP/UDP
IP
CLIP/SWITCH
AAL
SAR
QoS
DLC
Virtual Device
Physical Device




QoS Layer - Implementation



Experiments and Results


- Performance of the Flow Establishment Protocol
 - Throughput and flow setup time
 - Flow Re-establishment time
- Validity of the QoS Layer in RDRN
 - Absence & Presence of Congestion
 - Load testing
- Mobile QoS
 - Throughput





Flow Establishment Protocol Experiments and Results





Flow Establishment Time



Flow Establishment Vs. IP forwarding




Flow Re-establishment Logical Test Configuration



Flow Re-establishment Time


Distance of failing link from destination	Flow Re-establishment Time (in msec)
7	36.38
5	33.83
2	29.89



QoS Layer Validity Experiments




Test Configuration




Peak Cell Rate - 10Mbits/second



Weights of priorities - 5:3:2




WRR Scheduler - Single Flows





WRR Scheduler - Multiple Flows




High Priority under increasing load





“Weighted” Round Robin



Mobile QoS Experiments and Results




Test Scenario



End-to-end throughput

Single Flow

Sending Rate (in Mbits/second)	Receiving Rate (in Mbits/second)
3.6419	3.6417
3.5907	3.5905
3.6265	3.6265
3.6113	3.6095
3.6505	3.6499



End-to-end throughput

Multiple flows

Flow 1 - Priority 1

Flow 2 - Priority 2


Flow 1: Flow 2 = 5:2

Flow 1		Flow 2	
Sending Rate (in Mbits/second)	Receiving Rate (in Mbits/second)	Sending Rate (in Mbits/second)	Receiving Rate (in Mbits/second)
3.7761	3.6925	3.6419	3.0750
3.7481	3.6494	3.5905	3.1000
3.7766	3.6777	3.6312	3.0688
3.7588	3.7057	3.5769	3.0823



Conclusions

- A QoS architecture for highly dynamic networking environments like RDRN, has been proposed, implemented and evaluated.
- A flow establishment protocol tuned for IP-ATM mobile environments has been implemented and evaluated.
- A QoS Layer, which schedules the transmission of cells based on a WRR algorithm, has been introduced in the RDRN Protocol stack. Its validity has been tested.



Future Work

- Implement more scheduling algorithms and compare the performance.
- The scaling up feature that was discussed in the design has not been implemented. Since the framework is already available, this should be fairly easy.
- The handoff QoS parameters have not been used currently while doing the flow re-establishment.

